



US006934217B2

(12) **United States Patent**  
**Dutton et al.**

(10) **Patent No.:** **US 6,934,217 B2**  
(45) **Date of Patent:** **Aug. 23, 2005**

(54) **COUNTERMEASURE THREAT EMULATOR  
AND METHOD**

6,341,101 B1 \* 1/2002 Dutton et al. .... 367/1

(75) Inventors: **C. Ray Dutton**, New Bedford, MA (US); **Lynn A. Potter**, North Kingstown, RI (US); **Joseph B. Lopes**, Seekonk, MA (US)

(73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 919 days.

(21) Appl. No.: **09/780,367**

(22) Filed: **Feb. 13, 2001**

(65) **Prior Publication Data**

US 2004/0228213 A1 Nov. 18, 2004

(51) **Int. Cl.**<sup>7</sup> ..... **H04K 3/00**

(52) **U.S. Cl.** ..... **367/1**

(58) **Field of Search** ..... 367/1; 114/21.3;  
434/6, 10

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,192,245 A \* 3/1980 Kendig et al. .... 114/23  
5,235,924 A \* 8/1993 Slaton et al. .... 114/21.3

**OTHER PUBLICATIONS**

MacPherson, David., "Mk48 ADCAP Torpedo High-Assurance Testing," High Assurance Systems Engineering Workshop, Proceedings., IEEE, Oct. 1996, Niagara on the Lake, Ontario, Canada.\*

\* cited by examiner

*Primary Examiner*—Ian J. Lobo

(74) *Attorney, Agent, or Firm*—James M. Kasischke; Jean-Paul A. Nasser; Michael P. Stanley

(57) **ABSTRACT**

A system and method is disclosed for a countermeasure threat emulator (CME) provided in a tubular housing that may be launched from a submarine or ship. The CME electronics include a CPU board for running software, communicating with a computer external to the housing and data recording. The external computer preferably incorporates a database having data representative of a plurality of both foreign and domestic countermeasures. The data may be downloaded to the CPU board as well as updated for reprogramming of the CPU board. A digital signal processing board utilizes a plurality of DSP processors for running software capable of producing a wide range of acoustic signal outputs. A neural network may be used for analyzing and identifying acoustic sounds from incoming threats and notifying the CPU board for selection of a preprogrammed response for transmission by a transducer stack.

**15 Claims, 1 Drawing Sheet**

